

# Expand your horizons

Control the awning motor, adjust its opening to the millimeter

Control by remote, App, or voice

### REMOTE

A single remote for all actions



### APP



### VOICE



## Meet the A-OK Motors® range



Blinds



Wooden Venetian blinds



Roll-up mosquito nets



Adjustable roller blinds



Aluminum Venetian blinds



Interior Venetian blinds



Roll-up blinds



Projection screens



Traditional curtains



Vertical curtains



Folding blinds



Zip vertical curtains



Awnings



Vertical awnings



Pergolas



Windows



Lattice



Roll-up doors

## AM45 PLUS FSK WIFI®

## Create awnings with total control

Deploy a world of connections without a HUB thanks to our advanced bidirectionality, and achieve flawless performance thanks to our sensors

# A-OK®

cnaok5@aoksz.com  
www.a-okmotor.com

# A-OK®

cnaok5@aoksz.com  
www.a-okmotor.com

# Motorization, for all awnings

## More technology, more connectivity, more control: introducing the new generation of smart awnings

Designed for any type of awning, like invisible arm or cassette, it allows manual end position configuration or pressure closure. Thanks to its star-shaped head, it is compatible with all awning hardware.

### Ready to change the market game

Its powerful Wi-Fi integrated circuit allows a direct connection to your mobile phone or voice assistant, without the need for a HUB. Includes a quick connector for a superior installation.

Outstanding in security due to its back release function, which automatically adjusts the motor's force and performs a 1ms movement when closing by pressure, protecting the awning fabric. Furthermore, to ensure the integrity of the cassette and fabric, the motor will not perform a new pressure closure until after 25 cycles, and it adapts to the awning's size for a perfect pressure closure.

Finally, **bidirectionality in transmitters and sensors** ensures that the motor automatically retracts the awning in case of malfunctions.



### Features

- Ø 45 mm
- Electronic end limit
- Two programming options: double end limit or pressure closure for cassette awnings
- Bidirectionality with weather sensors
- Option to deactivate the solar sensor from the transmitter
- 5-meter extension wire to avoid additional splicing
- Options for 10, 15, and 20 meter wires
- Frequency 868.3 MHz
- Moisture-resistant surface




Bidirectional communication with **A-OK weather sensors** increases security in weather alarm situations, thanks to its ability for automatic and accurate data collection.



The new generation  
of motorization,  
for any awning



Direct connection



- Bidirectional Wi-Fi technology
- Removable **EASY CONNECT®** IP65 connector for easier installation

Percentage opening control



cnaok5@aoksz.com  
www.a-okmotor.com